

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
30 October 2003 (30.10.2003)

PCT

(10) International Publication Number
WO 03/089752 A2

- (51) International Patent Classification⁷: **E21B**
- (21) International Application Number: PCT/US03/11928
- (22) International Filing Date: 17 April 2003 (17.04.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/373,700 18 April 2002 (18.04.2002) US
60/373,701 18 April 2002 (18.04.2002) US
60/377,344 2 May 2002 (02.05.2002) US
- (71) Applicants and
(72) Inventors: VALENTI, Nicholas, P. [US/DK]; Ole Olsens
Alle 2, DK-2900 Hellerup (DK). VALENTI, Richard, M.
[US/US]; 1442 Kingwood Drive, PMB 157, Kingwood, TX
77339 (US).
- (74) Agent: CASPERSON, John, R.; P.O. Box 2174,
Friendswood, TX 77549 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: WELL COMPLETION WITH MERGED INFLUX OF WELL FLUIDS



(57) Abstract: The objective of the invention is to smoothly merge the influx flow streams with the wellbore flow stream so as to reduce the pressure drop along the perforated section of the wellbore liner. There is disclosed a completion liner for a well for the production of hydrocarbons is provided with angled ports through the sidewall which reduce pressure drop along the length of the liner. There is also disclosed short imperforate completion tubing for a well for the production of hydrocarbons is concentrically mounted alongside substantially only the perforated section of the production tubing to cause production fluids to initially flow toward the wellhead along an annulus defined between completion tubing and the production tubing prior to exiting the annulus and commingling with fluids produced from further down hole. There is further disclosed a completion casing for a well for the production of hydrocarbons which is provided with angled perforations through the casing sidewall which reduce flow resistance along the length of the casing.



WO 03/089752 A2